







Snow tank volume

1 m³ / compacted 1.25 m³
(35.3 ft³ / compacted 44.2 ft³)



Water tank volume 340 I (89.8 gal)



Blade width 1,400 mm (55 1/8 in)



Fields of operation Mobile / Event


GASOLINE





Engine	Honda GX690RH, 2 cylinder 688 cm ³ (41.9 in ³)
Power	16.5 kW / 22.1 HP - 3,600 rpm
Weight when empty	1,100 kg (2,425 lbs) – basic outfit
Water tank	340 I (89.8 gal)
Snow tank	1 m³ (35.3 ft³) – compacted 1.25 m³ (44.2 ft³)
Fuel tank	15 I (4 gal)

DIMENSIONS





STANDARD EQUIPMENT

Transmission	Continuously adjustable
Transmission	, ,
	hydraulic four-wheel drive
Axles	Single wheel drive
Steering	Hydraulic
Footbrake	Hydraulic
Parking brake	Mechanical parking brake
	on rear wheels
Hydraulic system	18 cm³ (0.004 gpm) axial piston pump
	for drive, 6 cm ³ (0.0013 gpm) work units +
	cylinder movements,
	4.4 cm³ (0.0001 gpm) steering
Diameter of	vertically ø 175 mm (6 7/8 in)
screw conveyors	horizontally ø 170 mm (6 5/8 in)
Tires	5.00R12 83/81P
	2 rows of spikes
Wheel rims	12" x 5" with hubcaps

All-wheel drive
Parking brakes
2 board guide rollers
Watertank-snowbin made of stainless steel
Spring suspended drivers seat
Horn
Easily accessible engine compartment (tiltable drivers
seat, hydraulically tiltable snowtank)
Hydraulic power steering
2 hydraulically powered screw conveyors
Hydraulic carriage pressure system
Hydraulic opening and closing of snow bin cover
Manual blade adjustment
Tiltable planing device for easy, safe blade changing
Tiltable operator's platform (2 positions)
1 blade
1 towel
Scope of delivery set










In conformity with Suva no. Nr. E 7164/1.e type-examination certificates





www.wm-on-ice.com Italy

WM ice technics relies on the following distribution partners in North America:



Autoworq

Montreal (Québec) Phone 1-866-973-1333 www.autoworq.com



LSK Enterprises

Virginia Beach (VA) Phone 1-757-366-0166 www.lskenterprises.com



Outdooricerinks.com

Strongsville (OH) Phone 1-440-628-7979 www.outdooricerinks.com





Mobile / Event

Pro / Heavy duty



Compact





